






档案员 Archivist
日期 Date

1	2	3	4	5	6	7	8	9	10	11							
H CONNECTOR PARAMETERS 连接器参数			版次 Rev.		ECN编号 ECN No.		修改说明 Reversion Description		设计 Designed		审核 Checked		核准 Approved				
G F E D C B A 3D MODEL / 3D模型																	
M12A-PM03S-SD (4-6) M12A-PM03S-SD (6-8)		M12A-PM04S-SD (4-6) M12A-PM04S-SD (6-8)		M12A-PM05S-SD (4-6) M12A-PM05S-SD (6-8)		M12A-PM08S-SD (4-6) M12A-PM08S-SD (6-8)											
孔位示意图 (3芯) HOLES ARRANGEMENT (3CORE)		孔位示意图 (4芯) HOLES ARRANGEMENT (4CORE)		孔位示意图 (5芯) HOLES ARRANGEMENT (5CORE)		孔位示意图 (8芯) HOLES ARRANGEMENT (8CORE)											
NOTE: OX :接触件PIN数。NUMBER OF CONTACTS . DX :适配电缆外径范围。THE RANGE OF CABLE OD SUITED .																	
自由公差 Free Tolerances		第三视角 3RD-Projection				单位 Unit		mm		名称 Name		重量 Weight		XXg			
长度尺寸 Length Dimensions X. ±0.20 . X ±0.10 . XX ±0.05		核准 Approved								M12A 3/4/5/8芯焊接型塑料弯头公插		材料 Material		/			
		审核 Checked								型号 Designation		M12A-PM0XS-SDXX		版本 Rev.		X1	
		工艺 Craft								图号 Figure No.		/					
角度 Angle X. ±1.0° . X ±0.5°		标检 Standarded								图面规格 Size		A4		比例 Scale		1:1	
		设计 Designed								页码 Sheet		1 / 1		 厦门固迈电气有限公司			