

档案员
Archivist

日期
Date

1	2	3	4	5	6	7	8	9	10	11			
CONNECTOR PARAMETERS 连接器参数			版次 Rev.	ECN编号 ECN No.	修改说明 Reversion Description			设计 Designed	审核 Checked	核准 Approved			
CONNECTION PARAMETERS 连接器参数													
			M12B-PF03S-SSHD (4-6)			M12B-PF04S-SSHD (4-6)			M12B-PF05S-SSHD (4-6)				
			M12B-PF03S-SSHD (6-8)			M12B-PF04S-SSHD (6-8)			M12B-PF05S-SSHD (6-8)				
			M12B-PF03S-SSHD (8-10)			M12B-PF04S-SSHD (8-10)			M12B-PF05S-SSHD (8-10)				
			孔位示意图 (3芯)			孔位示意图 (4芯)			孔位示意图 (5芯)				
			HOLES ARRANGEMENT (3CORE)			HOLES ARRANGEMENT (4CORE)			HOLES ARRANGEMENT (5CORE)				
			NOTE: 0X :接触件PIN数。NUMBER OF CONTACTS .										
			DXX :适配电缆外径范围。THE RANGE OF CABLE OD SUITED .										
			自由公差 Free Tolerances			第三视角 3RD-Projection		单位 Unit	mm	名称 Name	M12B 3/4/5芯焊接型金属弯头母插		
			长度尺寸 Length Dimensions X. ±0.20 .X ±0.10 .XX ±0.05			核准 Approved				型号 Designation	M12B-PF0XS-SSHDXX		
						审核 Checked				图号 Figure No.	/		
						工艺 Craft				图面规格 Size	A4	比例 Scale	1:1
			角度 Angle X. ±1.0° .X ±0.5°			标检 Standarded				页码 Sheet	1 / 1		
设计 Designed													
										重量 Weight XXg			
3D MODEL / 3D模型													
										材料 Material /			
										版本 Rev. X1			
厦门固迈电气有限公司													
1	2	3	4	5	6	7	8	9	10	11			

Gmatch

厦门固迈电气有限公司