


1	2	3	4	5	6	7	8	9	10	11				
H CONNECTOR PARAMETERS 连接器参数			版次 Rev.	ECN编号 ECN No.	修改说明 Reversion Description			设计 Designed	审核 Checked	核准 Approved				
G	F E D C B A										H			
M12B-PF03T-SSHD (4-6) M12B-PF03T-SSHD (6-8) M12B-PF03T-SSHD (8-10)								M12B-PF04T-SSHD (4-6) M12B-PF04T-SSHD (6-8) M12B-PF04T-SSHD (8-10)		M12B-PF05T-SSHD (4-6) M12B-PF05T-SSHD (6-8) M12B-PF05T-SSHD (8-10)				
孔位示意图 (3芯) HOLES ARRANGEMENT (3CORE)								孔位示意图 (4芯) HOLES ARRANGEMENT (4CORE)		孔位示意图 (5芯) HOLES ARRANGEMENT (5CORE)				
NOTE: OX :接触件PIN数。NUMBER OF CONTACTS . DX :适配电缆外径范围。THE RANGE OF CABLE OD SUITED .														
自由公差 Free Tolerances			第三视角 3RD-Projection		单位 Unit	mm	名称 Name	M12B 3/4/5芯螺钉型金属弯头母插			重量 Weight	XXg		
长度尺寸 Length Dimensions X. ±0.20 .X ±0.10 .XX ±0.05			核准 Approved				型号 Designation	M12B-PF OX T-SSHD XX			材料 Material	/		
			审核 Checked				图号 Figure No.	/			版本 Rev.	X1		
			工艺 Craft				图面规格 Size	A4	比例 Scale	1:1	 厦门固迈电气有限公司			
角度 Angle X. ±1.0° .X ±0.5°			标检 Standardized				页码 Sheet	1 / 1						
			设计 Designed											
1			2	3	4	5	6	7	8	9	10	11		



3D MODEL / 3D模型